

In-built clutch function in the wand hook to prevent breakages under force.

Robust Traveller Hooks

Superior performance with a heavy duty chain & thick cord.

# Deco Plus Verticals

Offering a superior level of style & performance

## Coordinated


- Contemporary headrail with subtle curved surfaces available in 6 colours, inspired by Australian home interior trends.
- Componentry, including cord, wand & handle, gears and end-caps, have been designed to blend seamlessly with headrails and coordinate with popular vertical fabrics.

## Uncomplicated

- Tracks are universal making it much easier to fabricate and install, including flipping on site if the control side needs to change.
- All stack options can be fabricated the same way, making for efficient manufacturing. Further efficiencies achieved with an integrated clutch function, preassembled speed nut and adjustable end retainers.

## Durable


- All components have been rigorously cycle tested to last up to 10 years.
- Endcaps, drive chain, travellers and end retainers forged from Polycetal, a highly engineered thermoplastic for precision and stability.



### Traversing Wand

With earless weights the traversing wand offers a child safe solution. Glide the wand across the track to open or close the blind, or spin the wand to tilt the louvres.

- Wand can be hidden behind the blades.
- Split stack options with a single wand.



### Chain & Cord

Conventional operation with a beaded continuous chain to tilt the louvres and a cord to open & close the blind.

## Technical Data

Size Limitations	89mm	100mm	127mm
Minimum width	300mm	300mm	300mm
Minimum drop	420mm	420mm	420mm
Maximum width	6000mm	6000mm	6000mm
Maximum drop	4000mm	4000mm	4000mm
Maximum area	16m <sup>2</sup>	18m <sup>2</sup>	24m <sup>2</sup>
Reveal depth	80mm	85mm	100mm
Fully recessed box mount	110mm	110mm	140mm
Bracket size on face fix	75mm	75mm	102mm
Minimum surface mount on face	50mm	50mm	50mm
Slat overlap	12mm	12mm	12mm
Stack calculations	$[(width / 77) \times 8] + 20$	$[(width / 88) \times 8] + 20$	$[(width / 115) \times 8] + 20$
<b>Sloping</b>	<b>Max drop</b>	<b>Max area</b>	
0 - 20 degrees	4000mm	15m <sup>2</sup>	
20 - 30 degrees	3000mm	10m <sup>2</sup>	
30 - 40 degrees	2750mm	6m <sup>2</sup>	
40 - 55 degrees	2500mm	3m <sup>2</sup>	
Light gaps	Idle end : 2mm	Control end : 5mm	Split stack with dual wand : 12mm
Track dimensions	<b>Height:</b> 25mm	<b>Depth:</b> 46mm	
Wands	Available in 5m lengths in Black, Gunmetal, White and Anodised for custom sizing.		
Chain & Cord	Black, Grey and Ivory chains available with tonal coordinated cord colours.		
Split stack dual wand	To minimise light gaps the left stack blades should be tilted in the opposite direction to the right stack.		
Child safe option	With earless weights the traversing wand offers a child safe solution.		
Deductions for track and spline	Chain & Cord: -13mm Wand: -7mm	} 3mm allowance	
Blade size	Opening Drop: - 38mm — If < 2 mts in drop, deduct a further 10mm Deductions If > 2 mts in drop, deduct a further 15mm		
Blade fold	Top Insert 25mm [12mm Pocket Size] Bottom Weight 63mm [55mm Pocket Size]		

Head rails are available in 6 colours:

